



Audible Telephone Call Signalling Sounder AS2



Features

- ▶ weatherproof telephone call sounder for universal applications in extreme industrial or other ambient conditions
- ▶ resistant against rain, humidity, heat, cold, acids, alkalis, greases etc.
- ▶ 4 tone types and tone frequencies selectable via DIP switch
- ▶ power supply via telephone call voltage
- ▶ works independently also during power failures



Technical data

Type	AS2
Housing, Colour	aluminium die cast, black RAL 9005 upper part polycarbonate, black RAL 9005
Mounting	wall or ceiling
Weight	0,5 kg
Call voltage	24 V AC - 75 V AC
Branch exchange voltage	0 V DC - 63 V DC
Input impedance	at 25 Hz $Z \geq 8 \text{ k}\Omega$ at 50 Hz $Z \geq 4 \text{ k}\Omega$
Acoustic signalling	loudspeaker
Tone types	single/two/three- and wobble tone selectable via DIP switch
Tone frequencies	5 to 20 Hz in 4 settings selectable via DIP switch
Terminal	1,5 mm ² single or fine wire
Cable entry	1 x M20x1,5
Insulation class	I



Order data

Type	Order No.	Denomination
AS2	410 200 004	Audible telephone call signalling sounder

Tone setting			
Tone Type	DIP Switch	Tone Sequence	
Single tone	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	180 ms on	70 ms off
	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	120 ms on	50 ms off
	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	60 ms on	25 ms off
	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	continuous tone	
Two tone	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	5 Hz	
	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	10 Hz	
	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	15 Hz	
	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	20 Hz	
Three tone	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	5 Hz	
	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	10 Hz	
	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	15 Hz	
	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	20 Hz	
Wobble tone	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	1,6 Hz	
	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	3,6 Hz	
	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	3,9 Hz	
	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	7,8 Hz	

